

Max Height ≤30m Ringlock Ledger with Vertical Load Capacity ≥45KN

Basic Information

Place of Origin: ChinaBrand Name: BythaiModel Number: BT03



Product Specification

Size: 48.3mmHorizontal Load ≥15KN

Capacity:

Warranty: 2 YearsVertical Load Capacity: ≥45KN

• Standard: EN12810 & EN12811

• Joints: Double-locking

Max Height: ≤30mVertical Adjustment: ≤±3°



More Images









Product Description:

Ringlock System Scaffolding is a versatile, cost-effective and safe scaffolding system used for building, repair, and maintenance, which is composed of a variety of components including verticals, horizontals, diagonals, braces, base plates, ladders, etc., made of Q235 steel with diameter 48.3mm. It is designed to meet the highest safety requirements and can support a maximum height of 30m and horizontal load capacity of 15KN. The system is easy to install and dismantle, and its superior stability, reliability and flexibility make it one of the most popular scaffolding systems in the market. With Ringlock formwork and Ringlock accessories, you can easily build a secure and strong scaffolding structure for any project.

Technical Parameters:

Parameter	Value
Product Name	Ringlock System Scaffolding
Material	Q235 Steel
Vertical Adjustment	<±3°
Size	48.3mm
Warranty	2 Years
Standard	EN12810 & EN12811
Weight	≤30kg/m2
Horizontal Adjustment	≤±3°
Surface Treatment	Hot-dip Galvanized
Max Height	≤30m
Horizontal Load Capacity	≥15KN

Applications:

Ringlock Scaffolding System is a versatile and cost-effective solution for those in need of scaffolding. Bythai's BT03 Ringlock System is designed with a $\pm 3^{\circ}$ horizontal and vertical adjustment, a size of 48.3mm, and a max height of up to 30m, enabling stability and safety during construction. The double-locking joints provide additional stability, ensuring maximum safety and reliability. Made in China, the BT03 Ringlock System is an excellent choice for those looking for a durable and efficient scaffolding system.

Customization:

Bythai BT03 Ringlock System Scaffolding

Brand Name: Bythai Model Number: BT03 Place of Origin: China Weight: ≤30kg/m2

Horizontal Load Capacity: ≥15KN Vertical Load Capacity: ≥45KN

Size: 48.3mm Joints: Double-locking

Bythai BT03 Ringlock System Scaffolding is the perfect choice for your construction needs. It is equipped with ringlock ledger, ringlock standard, and ringlock vertical, which provides you with strong and reliable support. The double-locking joints ensure the safety and security of the system. With a weight of ≤30kg/m2 and a vertical load capacity of ≥45KN, this scaffolding is a reliable and sturdy choice.

Packing and Shipping:

Packaging and Shipping of Ringlock System Scaffolding:

The Ringlock System Scaffolding will be securely packed with heavy-duty plastic wrap, paperboard/corrugated boxes or wood cases to protect the product from any damage during shipping.

Shipment of the product is usually done through air or sea. Depending on the customer's needs, we will work with different shipping companies to make sure the product is delivered in a safe and timely manner.

FAQ:

- Q1: What is the brand name of the Ringlock System Scaffolding?
- A1: The brand name of the Ringlock System Scaffolding is Bythai.
- Q2: What is the model number of the Ringlock System Scaffolding?

- A2: The model number of the Ringlock System Scaffolding is BT03.
- Q3: Where is the Ringlock System Scaffolding manufactured?
- A3: The Ringlock System Scaffolding is manufactured in China.
- Q4: What is the purpose of the Ringlock System Scaffolding?
- A4: The Ringlock System Scaffolding is used for construction projects, providing a secure and stable working platform.
- Q5: What are the advantages of the Ringlock System Scaffolding?
- A5: The Ringlock System Scaffolding is a fast and easy to install system with excellent load-bearing capacity. It is also highly durable and corrosion-resistant.



Bythai Scaffolding Co.,Ltd

17300780862

info@bythaiscaffolding.com

bythaiscaffold.com

No. 605, Industrail Exchange Center, Huanghua Town Changsha Hunan China